

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

-DT
LD

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS.

1. PART OR DRAWING NO. RCSK 18809 (34623)		2. CAGE 19207 34623		3. SPI NO. AK14773968	
4. NATIONAL STOCK NO. 2510-01-477-3968		5. DATE 04-17-01		6. REVISION	
7. QUP 1 EA.	8. ICQ NONE	9. UNIT PACK WT. 265.0		10. UNIT PACK CU 24.140	11. UNIT PACK SIZE 185.5 X 19.9 X 13.3
12. MILITARY PRESERVATION MIL-STD-2073-1C, METHOD 10		18. STEPS	19. REOD	20. DESCRIPTION	
13. CLEANING MIL-STD-2073-1C		1-B	2	BRACING: WOOD.	
14. DRYING MIL-STD-2073-1C		2-C	1	CONTAINER: PPP-B-621, CL. 2, STYLE 4, SIZE: 182-1/2 X 16-7/8 X 6-1/2, MOD.	
15. PACKING					
a. LEVEL A MIL-STD-2073-1C AND NOTE D					
b. LEVEL B NOT APPLICABLE					
16. MARKING MIL-STD-129					

17. NOTES/DRAWING
- A. PRESERVATION AND PACKING SHALL BE INSPECTED IN ACCORDANCE WITH MIL-STD-2073-1C.
 - B. FOR FABRICATION AND PLACEMENT OF BRACING SEE SKETCHES ON PAGE 2.
 - C. CONTAINER MODIFIED USING ONE INCH NOMINAL LUMBER, EXCEPT FOR SKID.
 - D. THE UNIT CONTAINER IS THE SHIPPING CONTAINER.

SPECIAL PACKAGING INSTRUCTION (Continuation Sheet)

Form Approved -DT
OMB No. 0704-0188 LD

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS.

1. PART OR DRAWING NO. RCSK 18809 (34623)	2. CAGE 19207 34623	3. SPI NO. AK14773968
4. NATIONAL STOCK NO. 2510-01-477-3968	5. DATE 04-17-01	6. REVISION

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. FABRICATE BRACE "A" USING PLYWOOD CONFORMING TO A-A-55057, TYPE A, EXPOSURE 1, 48/24 SPAN RATING, GRADE CDX, 3/4 INCH THICK. SECURE BRACE "A" TO INSIDE TOP OF CONTAINER USING FF-N-105, NO. 8 NAILS. SEE SKETCH BELOW.
3. FABRICATE BRACE "B" USING WOOD CONFORMING TO MIL-STD-731 GROUP II WOOD. SECURE BRACE "B" TO INSIDE TOP OF CONTAINER USING FF-N-105, NO. 8 NAILS. SEE SKETCH BELOW.

